

U-STAKE42, UNIVERSAL PEDESTAL MOUNTING STAKE

OVERVIEW

The Plugin Optics 42-Inch Universal Pedestal Stake provides a versatile and rigid deployment solution for pedestals. The Stake features adjustment heights from 22-Inch to 42-Inch, standard 1-Inch carriage bolt hole spacing, long channel slots on top for pedestal plate mounting, and additional 0.25-Inch side holes on top for cable management.

FEATURES

- Universal Design Supports Industry Standard Mounting Plates and Splicing Accessories
- Adjustable Length From 22-Inch to 42-Inch
- 0.5-Inch (Qty-2) and 0.75-Inch (Q2) M6 Carriage Bolts Included for Ease of Assembly and Pedestal Attachment
- Long Slots at Top for Pedestal Plate Mounting
- 0.25-Inch Holes Along the Top of the Stake to Provide Additional Cable Management Capabilities

APPLICATIONS

- Pedestal Installation
- Fiber Interconnect
- Fiber-To-The-Home, FTTH
- Fiber-To-The-Tower, FTTH



TECHNICAL SPECIFICATIONS

DESCRIPTION	UNITS	SPECIFICATION
DIMENSION: FULL STAKE (MAX)	in (mm)	42 (1066.8) x 1.5 (38.1) x 0.75 (19.1)
DIMENSION: STAKE BOTTOM	in (mm)	25.25 (641.4) x 1.5 (38.1) x 0.75 (19.1)
DIMENSION: STAKE TOP	in (mm)	19 (482.6) x 1.5 (38.1) x 0.75 (19.1)
MATERIAL	--	14GA STAINLESS STEEL
OPERATING TEMPERATURE	°C	-40 ~ +85
STORAGE TEMPERATURE	°C	-40 ~ +85

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
PLO-US-42	UNIVERSAL PEDESTAL STAKE, TWO PIECE, ADJUSTABLE LENGTH, 22-INCH TO 42-INCH

NOTE: PLUGIN OPTICS OFFERS A FULL LINE OF HARDWARE AND CONNECTIVITY SOLUTIONS.